



2026 MODIFIED DIMENSIONS

- A)** Window opening-12" min-18" max.
- B)** Front edge of roof to interior deck-11" min.
- C)** Rear edge of roof to interior deck-12" min.
- D)** Highest point of roof to ground-42" min-52" max.
- E)** Center of front wheel to front edge of front bumper-42".
- F)** Wheelbase: center of rear wheel to center of front wheel-108" min-112" max.
- G)** Center of rear wheel to front edge of door-72" max.
- H)** Center of rear wheel to rear edge of quarter panel-34" min-47 max.
- I)** Center of lowest bar on rear bumper to ground-16-20' max.
- J)** Deck height to ground-28" min-38" max.
- K)** Rear sail panel height 4" max.

- L)** Sail panel curve from rear of roof to rear of panel-2" max.
- M)** Sail panel bow from bottom to roof-2" max.
- N)** 2" max lip, same on both sides flush with hood.
- O)** 5" max drop (sides) sealed off from driver's compartment and max 6" rake.
- P)** 42" max nose must be flat and flush with sides.
- Q)** 67" max 42" min, must cover radiator
- R)** 53" max 32" min
- S)** 53" max 32" min
- T)** 67" max 55" min, measured at top of interior deck, must be same from back to front. Back of quarter panels 72" Max (measured at the bottom, plus six inches max on the left side door for tire clearance) 78" total
- U)** Width at the bottom of the doors (measured in front of rear tires) 72" Max

